


Towards Integrated Powertrain Control

Thermal Management of NG Heated Catalyst System

TNO | Knowledge for business



John Kessels
Darren Foster
Sebastian Bleuanus



26 November 2008


Outline Presentation




- Introduction Integrated Powertrain Control (IPC)
- Efficient powertrain development with IPC tools
 - Recognize interaction between subsystems
- Case study: IPC tools for catalyst heating
 - NG-engine with electrically heated catalyst system
 - System analysis
 - Heating strategy analysis
 - Measurement and simulation results
- Conclusions



- More stringent vehicle requirements and constraints:




- Increasing vehicle complexity owing to new advanced automotive technologies
- Tools required to handle system complexity and developing efficient powertrains:
 - >> Integrated Powertrain Control
 - Unified framework for developing control strategies incorporating all vehicle requirements
 - Exploit synergy between components
 - Optimal integration of subsystems




- Fast catalyst heating to reduce cold-start emissions
- Evaluate possible heating strategies
 - Ignition retard
 - Electric heated catalyst (in combination with hybrid powertrain)
- Consider fuel penalty for both heating methods
- Use IPC to analyze & develop heating strategy
- Vehicle configuration under consideration
 - Hybrid Electric Vehicle
 - Natural Gas engine
 - 3-way catalyst with electric heating

- Typical light-off profile for 3-way catalyst




- Most emissions appear during cold-start period
- Fast heating can improve overall exhaust emissions
- Required heating energy introduces fuel penalty



- How to select suitable heating strategy?
(ignition retard / electric heating)


- How to make fair comparison between different heating methods?
- IPC tools characterize fuel penalty and light-off time according to heating method
 - Measurement data characterizes ignition retard
 - Simulation results reveal potential for electric heating system
 - Validated simulation model used to characterize fuel sensitivity for electric energy from hybrid powertrain
- Final assessment of heating methods learns which method is preferred

- Ignition retard ϕ [$^{\circ}\text{CA}$] increases exhaust temperature




Measurement data:
NG-engine - 2.3L - 5 cylinders



- Electric heating can be applied in two ways
 - Direct heating of catalyst brick (heat transfer \Rightarrow conduction)
 - Indirect heating ahead of catalyst (heat transfer \Rightarrow convection)
- Current research considers only direct heating
 - Direct heating also works with engine stop
- Heating applied to first segment only
 - Reaction heat used for light-off downstream catalyst



- Ignition retard: ϕ [°CA]




- Electric heating power: P_e [W]







- Simulation model supports sensitivity analysis for (hybrid) vehicle parameters:

- Engine fuel map characteristics
- Power limits motor/generator
- Charge acceptance battery
- Battery losses
- Available regen-braking energy
- Vehicle driveability
- Energy management strategy
- ...



- All vehicle parameters are graphically visualized in an uncertainty area for fuel penalty ΔF_e





- Powertrain development with IPC tools
 - Handle system complexity
 - Efficient powertrain: integration of subsystems
- Case study presents IPC tools for catalyst heating
- Focus on fuel penalty, but emissions can be included in similar way
- IPC will be applicable to many other projects
 - E.g. DPF regeneration by increasing engine operating point with hybrid system